

APA6000 vs. EZ Series

The New Standard in Online Hardness Analysis

APA6000



NEW!

EZ Series



Features	APA6000	EZ Series Colorimeter	EZ Series Titrator
Multi-Stream Capabilities Monitoring multiple process streams in one instrument saves cost and wall space..	Max. 2 streams	Max. 8 streams	Max. 8 streams
Multi-Parameter Capabilities Monitoring multiple parameters provides a more complete picture of your process.	✗	Total Hardness Calcium Hardness Magnesium Hardn.	Total Hardness Calcium Hardness Free Alkalinity Total Alkalinity
Flexible Measuring Ranges Multiple selectable measuring ranges support high analytical performance and reliable results.	✗	✓	✓
Enhanced Connectivity Analog and digital communication outputs support easy integration into your systems.	✗	✓	✓
Wide Analytical Range A choice of different methods to match your lab method and your application needs.	✗	✓	✓
Service Protected All analyzers have a complete portfolio of service plans to help you protect your investment and peace of mind.	✓	✓	✓



Be Right™

Technical Specifications



Features	APA6000	EZ1000 Series Colorimeter	EZ4000/5000 Series Titrator
Parameter	Hardness	Total Hardness Calcium Hardness Magnesium Hardness	EZ4000 Single-Parameter: Total Hardness Calcium Hardness EZ5000 Multi-Parameter: Total Hardness Calcium Hardness Free Alkalinity Total Alkalinity
Measurement range (CaCO ₃)	0.05 - 10 mg/L 10 - 1000 mg/L	0.0025 - 0.1 mg/L 0.005 - 0.25 mg/L 0.005 - 0.5 mg/L 0.025 - 1 mg/L With internal dilution: 0.2 - 4 mg/L 0.4 - 8 mg/L 2.5 - 100 mg/L	0.25 - 10 mg/L (TH only) 10 - 100 mg/L 25 - 250 mg/L 50 - 500 mg/L 100 - 1000 mg/L Internal dispenser dilution (max. factor 100)
Limit of detection	1 mg/L CaCO ₃ 10 mg/L CaCO ₃	2.5 µg/L CaCO ₃	0.25 mg/L CaCO ₃ (TH only) 10 mg/L CaCO ₃
Accuracy	±5%	Better than 2% full scale range for standard test solutions	Better than 2% full scale range for standard test solutions
Outputs	2 x 4-20 mA outputs	Up to 8 x 4-20mA outputs Modbus RS485 Modbus TCP/IP	Up to 8 x 4-20mA outputs Modbus RS485 Modbus TCP/IP
Cycle Time	8.2 minutes for High Range 4 minutes for Low Range	10 minutes	10 - 15 minutes
Dimensions (HxWxD)	526 mm x 627 mm x 533 mm	690 mm x 465 mm x 330 mm	690 mm x 465 mm x 330 mm

Visit our website:
hach.com/ez-series

HACH COMPANY World Headquarters: Loveland, Colorado USA

United States: 800-227-4224 tel

970-669-2932 fax

orders@hach.com

Outside United States: 970-669-3050 tel

970-461-3939 fax

int@hach.com

hach.com

©Hach Company, 2020. All rights reserved.

In the interest of improving and updating its equipment, Hach Company reserves the right to alter specifications to equipment at any time.



Be Right™

DOC063.53.30647.Aug20